



Driginal post set 1821 by Laughlin with witnesses: 13" beech N 44 W 22 links, 30" ash S 49 E 30 links. Legal Survey 8-1854 by Wilson per Lawrence Township Legal Survey Book pg. 10 called stone at corner labels it "D". Distances given to W, N and E. Legal Survey by Smith 10-1866 per Lawrence Twp. Bk, pg. 13 called corner "H" gives distances W, S & E; but no info on corner. Legal Survey by Voorhis 10-1874 per Lawrence Twp. Bk pg. 13 called corner "N" called stone fd "set by former surveys legally recorded. Distance to W, S & E. 1921 ties by Mason called corner and distance to Q-Q corner to W; but no mention to the type of marker fd or set. 6-10-47 Walton called stone 8" dn. 10-3-73 Cripe, Inc. called PK in 1" angle iron over stone. 5-2-75 Fortner (MCS) reflect '73 Cripe ties as do 8-9-79 ties by Wilcoxen (MCS). '79 ties redrawn 3-5-82. 5-1-78 ties by D'Mahony /Miller Surv. notes stone w/faint 'x' fd 1' dn. PK nail in a pipe over stone per Cripe, Inc. Job#79110 called PK nail over stone fd per MCSD references. Distances & bearings given to corners S & W. Corner excavated 7-15-82 by Cleveland (MCS). PK nail fd to be inside 1" diameter, 6" long pipe 0.3' dn. Small stone 4"x6"x8" fd directly below the pipe 1.6' dn. Hole dug 30"deep and no other markers fd. Stone replaced with Harrison, set flush and backfilled hole.

HC752902

HC/52902				
REF.	DISTANCE	DESCRIPTION		
1.	41.52′	Rd nail SE PwP no# 8"up		
2.	39.71′	PK S PwP#136-251CA 6"up		
3,	-37.27′-	Sm. PK SW f.p. 12″up	Destroyed	
4.	-49.804-	Sm. PK SW f.p. 12"up	Destroyed	
5.	62.97'	Top nut		-
6.	65.03′	PK w/MCS brass washer SE PwP#77-251CB 20"up		
7.	38.72' RR spike S PwP#62-251CA 12"up			